

Details of Item(306046155)

Head

PACKING MATERIALS &  
HDPE/FRP/PVC & OTHER ITEMS.

Short Description: 50 LTR NON-ROLLING ROCKET

Specification

OXFORD BLUE COLOUR HM-HDPE  
NON-ROLLING ROCKET TYPE  
CARBUOYS OF 50 LITRES CAPACITY  
MATERIAL TO BE FILLED : 50 KGS  
HYDROGEN PEROXIDE (35% TO 70%)  
TYPE OF CARBUOYS REQUIRED:-  
NON ROLLOING ROCKET TYPE  
HM-HDPE CARBUOYS.  
NOMINAL VOLUME : 50 LTR.  
BRIM VOLUME : MINIMUM 52.5 LTR  
NO.OF OPENINGS : 1 NO.OPENING  
WITH BREATHER CAP WITH FILTER  
PAD & MUSHROOM CAP.  
NO.OF HANDLES : TWO AT SIDES.  
POSITION OF HANDLES SHALL BE  
INSIDE THE BODY.  
INSIDE REQUIREMENT : THOROUGHLY  
CLEANED FROM INSIDE & SHOULD  
HAVE SMOOTH INNER SURFACE.  
ZERO LEAK SEALING ARRANGEMENT  
TO BE PROVIDED.  
BREATHER CAP COLOUR : YELLOW  
CAP SEALING : ALL CAPS ARE  
REQUIRED WITH ATTACHED SEALING  
ARRANGEMENT.  
THREADS OF NECK AND CAP SHALL  
BE AS PER ATTACHED SKETCH.  
DIMENSION OF CARBUOYS  
L X B X H IN MM  
380 X 330 X 570 (+/- 2%)  
CAP SHALL BEAR GAEL NAME.  
EMBOSSING REQUIREMENT :-  
1. ON CARBUOYS :-  
MONTH & YEAR OF MANUFACTURE  
LOGO & NAME OF MANUFACTURER  
LOGO & NAME OF GAEL  
SPACE FOR UN NUMBER.  
2. ON CAPS :-  
MONTH & YEAR OF MANUFACTURE  
MANUFACTURER LOGO,  
LABEL CLASS : 5.1  
SUBSIDIARY RISK LABEL OF  
CLASS : 8  
UN NUMBER : PAGE : 5151  
ADMT : 27-97  
I.S.STANDARD : IS 6312 EXCEPT  
DROP TEST.  
DROP TEST SHALL BE CARRY OUT  
FROM 3.0 MTR HEIGHT.  
WEIGHT OF CARBUOY:2.4 KG.+/-2%  
STANDARD TEST REQUIRED AS PER  
I.S. & UN NO.  
- APPEARANCE  
- DROP TEST  
- HYDRAULIC TEST  
- LEAKAGE TEST  
- STACK LOAD TEST  
-MEMBRANE TEST

306046155.txt

Approx. Annual Requirement: 54000 Nos

Approx. Monthly Consumption: 45000 Nos